



GALLERY



THRILL SlimPAR Mini LED

THRILL SlimPAR Mini LED, packs a wallop of light for its small size. This LED fixture will illuminate your party or event with full, intense and saturated colors. Seven 3-watt RGB LEDs give a uniform field of light that is perfect for wall washes, truss toning and front or back lighting. The sit-flat design makes the light easy to slide under tables, tuck inside a truss or into any tight spot.

The THRILL SlimPAR Mini LED features 36 vibrant, pre-programmed colors and full RGBWA+UV color mixing so that any color in the spectrum can be created. Combine this wide color palette with electronic strobe/dimming and the THRILL SlimPAR Mini LED will take your event from great to brilliant. An included wireless remote control makes programming a breeze, simply point and click to get the color you want or run the pre-programmed settings.

Its lightweight design, super-slim profile and wireless remote control make it the perfect fit and a safe all-around choice for on-the-go entertainers, DJs, venues and home enthusiasts that require professional lighting at an affordable price.

Portable, lightweight and easy to control

Sit-flat design allows versatile fixture placement

Plug-and-play functionality with easy-to-use remote control

FEATURES

- Uniform field of light via 7 x 3 W RGB LEDs
- Fixed 25° beam angle
- 36 vibrant pre-programmed colors
- Dynamic effects include color mixing, strobe, dimmer
- Remote control included for quick color selection
- Easy to operate standalone sound-activated, master/slave control methods
- 4 professionally pre-programmed shows
- DMX operable for individualized control and design
- Included adjustable bracket for hanging or surface mount
- Common IEC mains inlet/thru – mains cable included

TECHNICAL SPECIFICATIONS

Physical

Length: 229 mm (9 in.)

Width: 115 mm (4.5 in.)

Height: 229 mm (9 in.)

Maximum footprint standing: 229 mm (9 in.) x 204 mm (8 in.)

Weight: 1.3 kg (2.9 lb.)

Dynamic Effects

Color mixing: RGB

Color selection: 36 color presets

Electronic dimming: 0 – 100 %

Strobe and pulse effects: Variable speed and action, random strobe

Electronic 'shutter' effect: Instant open and blackout

Control and Programming

Control options: DMX, stand-alone, IR remote control

DMX channels: 3/6

Stand-alone trigger options: Sound-trigger, auto-run

User interface: Control panel with LCD display

DMX compliance: ANSI E1.11 - USITT DMX512-A

Optics

Light source: 7 x 3 W RGB LEDs

Minimum LED lifetime: 30 000 hours (to >70% luminous output)*

**Figure obtained under manufacturer's test conditions*

Construction

Housing: High-impact flame-retardant thermoplastic

Color: Black

Protection rating: IP20

Installation

Mounting: Adjustable bracket, surface or truss mount

Mounting points: Bracket for single rigging clamp, M12 or ½"

Orientation: Any

Location: Indoor use only

Connections

AC power in/thru: IEC male inlet/female connector, C14/C13

DMX data in/thru: 3-pin XLR

Electrical

AC power: 100-240 V nominal, 50/60 Hz

Fuse: F 3AL, 250V

Typical total power consumption: 25 W

Maximum fixtures on AC power throughput, 100-130 V: 10 THRILL SlimPAR Mini LED or 3 A

Maximum fixtures on AC power throughput, 220-240 V: 15 THRILL SlimPAR Mini LED or 3 A

Power consumption figures are typical, not maximum. Allow for +/-10% variation.

Typical Power and Current

110 V, 60 Hz: 0.3 A, 30 W *

230 V, 50 Hz: 0.2 A, 30 W *

**Measurements made at nominal voltage with all LEDs at full intensity. Allow for a deviation of +/- 10%.*

Thermal

Cooling: Passive

Maximum ambient temperature (Ta max.): 40° C (104° F)

Minimum ambient temperature (Ta min.): 0° C (32° F)

Total heat dissipation (calculated, +/- 10%, at full intensity, full white): 85 BTU/hr.

Approvals

EU safety: EN 60598-1, EN 60598-2, EN 62031, EN 62471, EN 62493

EU EMC: EN 55015, EN 61000-3-2, EN 61000-3-3, EN 61547

Included Items

Power cable, EU, IEC C13 female, molded Schuko, 1.5 m (6.3 ft.)

Power cable, US, IEC C13 female, molded NEMA 5-15P, 1.5 m (6.3 ft.)

Multi-function bracket

IR remote control: P/N TBA

Accessories

Installation hardware

Super lightweight half coupler, black: P/N 91602018

Safety cable, SWL 60kg (132 lb.), BGV C1/ DGUV 17, black: P/N 91604006

Related Items

Martin M-Touch™: P/N 90737040

Martin M-Play™: P/N 90737030

Ordering Information

THRILL™ SlimPAR Mini LED: P/N 90280115

