



## iSeries 2217-8 Case



SKB iSeries Injection Molded Mil-Standard Waterproof Cases are molded of ultra high-strength polypropylene copolymer resin, featuring a gasket-sealed, water and dust tight, submersible design (MIL-STD 810H) that is resistant to corrosion and impact damage. Standard features include a molded-in hinge, padlock loops, Trigger Latch® System, snap-down rubber over-molded cushion grip handle, automatic ambient pressure equalization valve (MIL-STD 810H), and resistance to UV, solvents, corrosion, fungus and impact damage (MIL-STD 810H).

### Features

- Ultra high-strength polypropylene copolymer resin
- UV, solvent, corrosion and fungus resistant (MIL-STD 810H)
- Complete gasket seal makes these cases absolutely watertight (MIL-STD 810H)
- Automatic ambient pressure equalization valve (MIL-STD 810H)
- Resistant to corrosion and impact damage
- Continuous molded-in hinge
- Trigger Latch® System
- Rubber over-molded cushion grip handle
- Locking loops to accept a customer supplied lock

| Specification              | Imperial | Metric   |
|----------------------------|----------|----------|
| Exterior                   | Hard     |          |
| Built In Wheels or Casters | No       |          |
| Interior Length            | 22 in    | 55.88 cm |
| Interior Width             | 17 in    | 43.18 cm |
| Interior Lid Depth         | 2 in     | 5.08 cm  |
| Interior Base Depth        | 5.875 in | 14.92 cm |
| Exterior Length            | 24.32 in | 61.77 cm |
| Exterior Width             | 19.5 in  | 49.53 cm |

| Specification   | Imperial | Metric    |
|-----------------|----------|-----------|
| Exterior Height | 8.88 in  | 22.56 cm  |
| Carton Length   | 24.5 in  | 62.23 cm  |
| Carton Width    | 20 in    | 50.80 cm  |
| Carton Height   | 9.5 in   | 24.13 cm  |
| Product Weight  | 11.12 lb | 5.04 kg   |
| Shipping Weight | 12.88 lb | 5.84 kg   |
| Max Temp        | 180 °F   | 82.22 °C  |
| Min Temp        | -69 °F   | -56.11 °C |