



4U 24-inch Deep RR Series Shock Rack



SKB's 3RR Series Removable Shock Rack Transport cases that are available in 7 sizes, 3U, 4U, 5U, 7U, 9U, 11U and 14U. These new Shock Racks are lightweight, shockproof, watertight, dust proof, heat and chemical resistant, perfect for protecting and transporting your sensitive electronic equipment.

Molded of LMDP Linear Medium Density Polyethylene plastic that meets or exceeds MIL-STD 810H standards and includes 8 elastomeric shock absorbers which allows a standard payload range of 40 to 150 pounds. Optional extended payload range of 160 to 300 pounds can be accommodated as a special order option—must be installed by SKB. The 3RR Series Removable Racks are 24" deep from rail to rail with a standard 19" rack width per EIA/ECA-310-E specification and feature square-hole rack rails to accommodate either #10-32 US standard, or 6mm International standard cage nuts which are supplied with the cases.

The rugged roto-molded shell ensures industry leading strength and impact resistance. The standard COTS (commercial off the shelf) case comes with a 2" deep front lid and a 5" deep rear lid to accommodate rack gear that is longer than 24", and edge casters to allow convenient case transport. Molded-in stacking ribs and lugs are designed to stack with competitive manufacturers cases. Black powder coated stainless steel hardware are recessed for protection is standard as well as 8 comfort grip spring loaded lift handles which allow for easy movement. An automatic pressure relief valve is another standard feature along with gasket sealed lids that include convenient lid hangers to store your lids when your equipment is in operation. Coupling straps are included for securing the racks together when stacked.

The interior of the case features a removable rack with a patented "positive lock" latching system that slides open like a file drawer, allowing full access to racked equipment. The interior rack is also completely removable allowing complete frame access for bench integration.

Standard color is Black, also available in Desert Tan or OD Green.

Note: The payload for standard shock absorbers is 40 - 150 lbs. Additional shock absorbers can be added to increase the payload to 160 - 300 lbs, however, these can only be installed by SKB. Please contact us for more information.

Features

- Completely removable frame for access to bench integration

Meets or Exceeds MIL-STD 810H

Standard payload range 40 to 150 lbs

Optional extended payload range 160 to 300 lbs.

Standard 19" Rack width per EIA/ECA-310-E

Standard Rack depth 24" rail to rail,

Square hold rack rails to accommodate either #10-32 US standard, or 6mm international standard cage nuts

2" front lid, and 5" rear lid with edge casters standard, other options available

SKB's Rugged roto-molded shell ensures industry leading strength and impact resistance

Molded in stacking ribs and lugs are designed to stack with competitive manufacturers cases

Black powder coated stainless steel hardware (standard) which are recessed for protection

8 comfort grip spring loaded lift handles

Automatic pressure relief valve (standard)

Lid hangars (standard)

Case coupling straps (standard)

Specification	Imperial	Metric
Exterior	Hard	
Built In Wheels or Casters	Yes	
Exterior Length	39 in	99.06 cm
Exterior Width	24 in	60.96 cm
Exterior Height	13.25 in	33.66 cm
Carton Length	40 in	101.60 cm
Carton Width	24.5 in	62.23 cm
Carton Height	14.5 in	36.83 cm
Product Weight	59.51 lb	26.99 kg
Shipping Weight	63.7 lb	28.89 kg
Max Temp	0 °F	-17.78 °C
Min Temp	0 °F	-17.78 °C