



## iSeries 1510-6 Case



SKB iSeries Injection Molded Mil-Standard Waterproof Cases are molded of ultra high-strength polypropylene copolymer resin, featuring a gasket-sealed, water and dust tight, submersible design (MIL-STD 810H) that is resistant to corrosion and impact damage.

Standard features include a molded-in hinge, Trigger Latch® System, snap-down rubber over-molded cushion grip handle, automatic ambient pressure equalization valve (MIL-STD 810H), and resistance to UV, solvents, corrosion, fungus and impact damage (MIL-STD 810H).

### Features

- Waterproof and dust tight design (MIL-STD 810H)
- Molded-in hinge for added protection  
Trigger Latch® System  
Snap-down rubber over-molded cushion grip handle  
Ambient pressure equalization valve (MIL-STD 810H)  
Resistant to UV, solvents, corrosion, fungus and impact damage (MIL-STD 810H)

| Specification              | Imperial  | Metric   |
|----------------------------|-----------|----------|
| Exterior                   | Hard      |          |
| Built In Wheels or Casters | No        |          |
| Interior Length            | 15 in     | 38.10 cm |
| Interior Width             | 10.5 in   | 26.67 cm |
| Interior Lid Depth         | 1.625 in  | 4.13 cm  |
| Interior Base Depth        | 4.25 in   | 10.79 cm |
| Exterior Length            | 16.25 in  | 41.27 cm |
| Exterior Width             | 12.875 in | 32.70 cm |
| Exterior Height            | 6.75 in   | 17.14 cm |

| Specification   | Imperial | Metric    |
|-----------------|----------|-----------|
| Carton Length   | 17 in    | 43.18 cm  |
| Carton Width    | 13.5 in  | 34.29 cm  |
| Carton Height   | 7.5 in   | 19.05 cm  |
| Product Weight  | 5.19 lb  | 2.35 kg   |
| Shipping Weight | 6.07 lb  | 2.75 kg   |
| Max Temp        | 180 °F   | 82.22 °C  |
| Min Temp        | -69 °F   | -56.11 °C |