



14U 24-inch Deep RS Series Shock Rack



SKB's 3RS Series Static Shock Rack Transport cases are available in 7 sizes, 3U, 4U, 5U, 7U, 9U, 11U and 14U. These Static Shock Racks are lightweight, shockproof, watertight, dustproof, heat and chemical resistant, perfect for protecting and transporting your sensitive electronic equipment.

Molded of LMDP Linear Medium Density Polyethylene plastic that meets or exceeds MIL-STD 810H standards and includes 8 elastomeric shock absorbers which allows a standard payload range of 40 to 150 pounds. Optional extended payload range of 160 to 300 pounds can be accommodated as a special order option—must be installed by SKB. The 3RS Series Static Shock Racks are available in 24" or 30" deep from rail to rail with a standard 19" rack width per EIA/ECA-310-E specification and feature square-hole rack rails to accommodate either #10-32 US standard, or 6mm International standard cage nuts which are supplied with the cases.

The rugged roto-molded shell ensures industry leading strength and impact resistance. The standard COTS (commercial off the shelf) case comes with a 2" deep front lid and a 5" deep rear lid to accommodate rack gear that is longer than 24", and edge casters to allow convenient case transport. Molded-in stacking ribs and lugs are designed to stack with competitive manufacturers cases. Black powder coated stainless steel hardware are recessed for protection is standard as well as 8 comfort grip spring loaded lift handles which allow for easy movement. An automatic pressure relief valve is another standard feature along with gasket sealed lids that include convenient lid hangers to store your lids when your equipment is in operation. Coupling straps are included for securing the racks together when stacked.

Note: The payload for standard shock absorbers is 40 - 150 lbs. Additional shock absorbers can be added to increase the payload to 160 - 300 lbs, however, these can only be installed by SKB. Please contact us for more information.

Features

- Meets or Exceeds MIL-STD 810H
- Standard payload range 40 to 150 lbs
- Optional extended payload range 160 to 300 lbs.
- Standard 19" Rack width per EIA/ECA-310-E
- Standard Rack depth 24" rail to rail
- Square hole rack rails to accommodate either #10-32 US standard, or 6mm international standard cage nuts
- 2" front lid, and 5" rear lid with edge casters standard, other options available
- SKB's Rugged roto-molded shell ensures industry leading strength and impact resistance
- Molded in stacking ribs and lugs are designed to stack with competitive manufacturers cases
- Black powder coated stainless steel hardware (standard) which are recessed for protection
- 8 comfort grip spring loaded lift handles
- Automatic pressure relief valve (standard)
- Lid hangers (standard)
- Case coupling straps (standard)
- Reduced Footprint
- Low Profile
- Light Weight
- Lifetime Warranty

Specification	Imperial	Metric
Exterior	Hard	
Built In Wheels or Casters	Yes	
Exterior Length	38.75 in	98.42 cm
Exterior Width	31 in	78.74 cm
Exterior Height	24 in	60.96 cm
Carton Length	40 in	101.60 cm
Carton Width	31.5 in	80.01 cm
Carton Height	24.5 in	62.23 cm
Product Weight	79.55 lb	36.08 kg
Shipping Weight	86.53 lb	39.25 kg
Max Temp	0 °F	-17.78 °C
Min Temp	0 °F	-17.78 °C