



9U 20-inch Deep RR Series Shock Rack



SKB's 3RR Series Removable Shock Rack Transport cases are available in 8 sizes: 3U, 4U, 5U, 6U, 7U, 9U, 11U and 14U. These Shock Racks are lightweight, shockproof, watertight, dustproof, heat and chemical resistant, perfect for protecting and transporting your sensitive electronic equipment.

Molded of LMDP Linear Medium Density Polyethylene plastic that meets or exceeds MIL-STD 810H standards, these Shock Racks also include 8 elastomeric shock absorbers which allow for a standard payload range of 40 to 150 lbs (optional extended payload range of 160 to 300 lbs can be accommodated as a special order option—must be installed by SKB). The 20" 3RR Series Removable Racks are 20" deep from rail to rail with a standard 19" rack width per EIA/ECA-310-E specification and feature square-hole rack rails to accommodate either #10-32 US standard or 6mm International standard cage nuts which are supplied with the cases.

The rugged roto-molded shell ensures industry leading strength and impact resistance. The standard commercial off the shelf (COTS) case comes with 2" deep front and rear lids to accommodate rack gear that is longer than 20". Molded-in stacking ribs and lugs are designed to stack with all SKB 3RR and 3RS cases, as well as competitive manufacturer cases, and feature black powder coated stainless steel hardware that is recessed for protection and 4 comfort grip spring loaded lift handles which allow for easy movement. An automatic pressure relief valve is another standard feature along with gasket sealed lids that include convenient lid hangers to store your lids when your equipment is in operation. Coupling straps are included for securing the racks together when stacked.

The interior of the case features a removable rack with a patent pending "positive lock" latching system that slides open like a file drawer, allowing full access to racked equipment. The interior rack is also completely removable allowing complete frame access for bench integration.

Available in Black (standard), Desert Tan, and OD Green.

Notes: 3RR 20" Shock Racks do not come standard with wheels; please see the 3RR-RCB Shock Rack Caster Platform in the accessories tab for an alternative.

The payload for standard shock absorbers is 40 - 150 lbs. Additional shock absorbers can be added to increase the payload to 160 - 300 lbs, however, these can only be installed by SKB. Please contact us for more information.

Features

- Completely removable frame for access to bench integration

Meets or exceeds MIL-STD 810H

Standard payload range of 40 to 150 lbs

Optional extended payload range 160 to 300 lbs

Standard 19" rack width per EIA/ECA-310-E

Standard rack depth 20" rail to rail

Square hole rack rails to accommodate either #10-32 US standard or 6mm international standard cage nuts

2" front and rear lids

Rugged roto-molded shell ensures industry leading strength and impact resistance

Molded in stacking ribs and lugs are designed to stack with all SKB 3RR & 3RS cases, as well as competitive manufacturer cases

Recessed black powder coated stainless steel hardware

Four (4) comfort grip spring loaded lift handles

Specification	Imperial	Metric
Exterior	Hard	
Built In Wheels or Casters	No	
Exterior Length	31.5 in	80.01 cm
Exterior Width	24 in	60.96 cm
Exterior Height	22.25 in	56.52 cm
Carton Length	32 in	81.28 cm
Carton Width	24.5 in	62.23 cm
Carton Height	22.5 in	57.15 cm
Product Weight	61.56 lb	27.92 kg
Shipping Weight	67.04 lb	30.41 kg
Max Temp	180 °F	82.22 °C
Min Temp	-40 °F	-40.00 °C